

Advantage Products 优势产品

TVS系列

现今您可以将冲击波的问题，交给本公司低电容突波吸收器，将限制瞬间过高的电压“Transient Voltage Suppressors”(TVS) (瞬间电压冲击波抑制)，提高机器设备的使用年限和系统的可靠性，使您不再为闪电、打雷而担心机器设备被破坏，目前本公司提供200W、400W、600W、1500W、5000W之 6.8V至400V A/CA(单向及双向)产品，并可客制尺寸及提供刀刮及光刻 GPP两种制程晶粒。

FEATURE

- Low power loss
- High surge capability
- Glass passivated chip junction
- Available in Unidirectional and Bidirectional (For Bidirectional types, use A or CA suffix, e.g. P6KE400CA)
- Ultra-fast recovery time for high efficiency
- High temperature soldering guaranteed

标准晶粒规格表

Chip size	Package
45	P2
60	P4KE, BZW04, SMAJ, P4SMA
70	SMA, SMA5J, P4SMA
80	P6KE, SMBJ, P6SMB
90	SMB8J
114	SMCJ
125	1P5KE, 1P5SMC

600W电性表

MAXIMUM RATINGS (TA = 25 ° C unless otherwise noted)				
	PARAMETER	Symbol	VALUE UNI	units
	Peak power dissipation with a 10/1000 μs waveform	P _{PPM}	600	W
	Peak pulse current with a 10/1000 μs waveform	I _{PPM}	see next table	A
	Power dissipation on infinite heatsink at T _L = 75 ° C	P _D	5.0	W
	Peak forward surge current, 8.3 ms single half sine-wave unidirectional only	I _{FSM}	100	A
	Maximum instantaneous forward voltage at 50A for unidirectional only	V _F	3.5/5.0	V
	Typical thermal resistance junction-to-lead	R _{th(jl)}	20	°C/W
	Typical thermal resistance junction-to-ambient	R _{th(ja)}	75	°C/W
	Storage and Operating Junction Temperature	T _{stg} , T _j	-55 to +175	°C

DEVICE TYPE	BREAKDOWN VOLTAGE $V_{(BR)}$ (V) @ $I_T^{(1)}$		TEST CURRENT I_T (mA)	STAND-OFF VOLTAGE V_{WM} (V)	MAXIMUM REVERSE LEAKAGE I_D (μ A) @ V_{WM}	PEAK PULSE CURRENT I_{PPM} (A) ⁽²⁾	MAXIMUM CLAMPING VOLTAGE V_C (V) @ I_{PPM}
	MIN	MAX					
P6KE6.8	6.12	7.48	10	5.50	1000	55.6	10.8
P6KE6.8A	6.45	7.14	10	5.80	1000	57.1	10.5
P6KE7.5	6.75	8.25	10	6.05	500	51.3	11.7
P6KE7.5A	7.13	7.88	10	6.40	500	53.1	11.3
P6KE8.2	7.38	9.02	10	6.63	200	48.0	12.5
P6KE8.2A	7.79	8.61	10	7.02	200	49.6	12.1
P6KE9.1	8.19	10.0	1.0	7.37	50	43.5	13.8
P6KE9.1A	8.65	9.55	1.0	7.78	50	44.8	13.4
P6KE10	9.00	11.0	1.0	8.10	10	40.0	15.0
P6KE10A	9.50	10.5	1.0	8.55	10	41.4	14.5
P6KE11	9.90	12.1	1.0	8.92	5.0	37.0	16.2
P6KE11A	10.5	11.6	1.0	9.40	5.0	38.5	15.6
P6KE12	10.8	13.2	1.0	9.72	5.0	34.7	17.3
P6KE12A	11.4	12.6	1.0	10.2	5.0	35.9	16.7
P6KE13	11.7	14.3	1.0	10.5	5.0	31.6	19.0
P6KE13A	12.4	13.7	1.0	11.1	5.0	33.0	18.2
P6KE15	13.5	16.5	1.0	12.1	1.0	27.3	22.0
P6KE15A	14.3	15.8	1.0	12.8	1.0	28.3	21.2
P6KE16	14.4	17.6	1.0	12.9	1.0	25.5	23.5
P6KE16A	15.2	16.8	1.0	13.6	1.0	26.7	22.5
P6KE18	16.2	19.8	1.0	14.5	1.0	22.6	26.5
P6KE18A	17.1	18.9	1.0	15.3	1.0	23.8	25.2
P6KE20	18.0	22.0	1.0	16.2	1.0	20.6	29.1
P6KE20A	19.0	21.0	1.0	17.1	1.0	21.7	27.7
P6KE22	19.8	24.2	1.0	17.8	1.0	18.8	31.9
P6KE22A	20.9	23.1	1.0	18.8	1.0	19.6	30.6
P6KE24	21.6	26.4	1.0	19.4	1.0	17.3	34.7
P6KE24A	22.8	25.2	1.0	20.5	1.0	18.1	33.2
P6KE27	24.3	29.7	1.0	21.8	1.0	15.3	39.1
P6KE27A	25.7	28.4	1.0	23.1	1.0	16.0	37.5
P6KE30	27.0	33.0	1.0	24.3	1.0	13.8	43.5
P6KE30A	28.5	31.5	1.0	25.6	1.0	14.5	41.4
P6KE33	29.7	36.3	1.0	26.8	1.0	12.6	47.7
P6KE33A	31.4	34.7	1.0	28.2	1.0	13.1	45.7
P6KE36	32.4	39.6	1.0	29.1	1.0	11.5	52.0
P6KE36A	34.2	37.8	1.0	30.8	1.0	12.0	49.9
P6KE39	35.1	42.9	1.0	31.6	1.0	10.6	56.4
P6KE39A	37.1	41.0	1.0	33.3	1.0	11.1	53.9
P6KE43	38.7	47.3	1.0	34.8	1.0	9.7	61.9
P6KE43A	40.9	45.2	1.0	36.8	1.0	10.1	59.3
P6KE47	42.3	51.7	1.0	38.1	1.0	8.8	67.8
P6KE47A	44.7	49.4	1.0	40.2	1.0	9.3	64.8
P6KE51	45.9	56.1	1.0	41.3	1.0	8.2	73.5
P6KE51A	48.5	53.6	1.0	43.6	1.0	8.6	70.1
P6KE56	50.4	61.6	1.0	45.4	1.0	7.5	80.5
P6KE56A	53.2	58.8	1.0	47.8	1.0	7.8	77.0
P6KE62	55.8	68.2	1.0	50.2	1.0	6.7	89.0
P6KE62A	58.9	65.1	1.0	53.0	1.0	7.1	85.0

DEVICE TYPE	BREAKDOWN VOLTAGE $V_{(BR)}$ (V) @ $I_T^{(1)}$		TEST CURRENT I_T (mA)	STAND-OFF VOLTAGE V_{WM} (V)	MAXIMUM REVERSE LEAKAGE I_D (μ A) @ $V_{WM}^{(3)}$	PEAK PULSE CURRENT I_{PPM} (A) ⁽²⁾	MAXIMUM CLAMPING VOLTAGE V_C (V) @ I_{PPM}
	MIN	MAX					
P6KE68	61.2	74.8	1.0	55.1	1.0	6.1	98.0
P6KE68A	64.6	71.4	1.0	58.1	1.0	6.5	92.0
P6KE82	73.8	90.2	1.0	66.4	1.0	5.1	118
P6KE82A	77.9	86.1	1.0	70.1	1.0	5.3	113
P6KE91	81.9	100	1.0	73.7	1.0	4.6	131
P6KE91A	86.5	95.5	1.0	77.8	1.0	4.8	125
P6KE100	90.0	110	1.0	81.0	1.0	4.2	144
P6KE100A	95.0	105	1.0	85.5	1.0	4.4	137
P6KE110	99.0	121	1.0	89.2	1.0	3.8	158
P6KE110A	105	116	1.0	94.0	1.0	3.9	152
P6KE120	108	132	1.0	97.2	1.0	3.5	173
P6KE120A	114	126	1.0	102	1.0	3.6	165
P6KE130	117	143	1.0	105	1.0	3.2	187
P6KE130A	124	137	1.0	111	1.0	3.4	179
P6KE140	126	154	1.0	112	1.0	3.0	200
P6KE140A	133	147	1.0	119	1.0	3.1	192
P6KE150	135	165	1.0	121	1.0	2.8	215
P6KE150A	143	158	1.0	128	1.0	2.9	207
P6KE160	144	176	1.0	130	1.0	2.6	230
P6KE160A	152	168	1.0	136	1.0	2.7	219
P6KE170	153	187	1.0	138	1.0	2.5	244
P6KE170A	162	179	1.0	145	1.0	2.6	234
P6KE180	162	198	1.0	146	1.0	2.3	258
P6KE180A	171	189	1.0	154	1.0	2.4	246
P6KE200	180	220	1.0	162	1.0	2.1	287
P6KE200A	190	210	1.0	171	1.0	2.2	274
P6KE220	198	242	1.0	175	1.0	1.7	344
P6KE220A	209	231	1.0	185	1.0	1.8	328
P6KE250	225	275	1.0	202	1.0	1.7	360
P6KE250A	237	263	1.0	214	1.0	1.7	344
P6KE300	270	330	1.0	243	1.0	1.4	430
P6KE300A	285	315	1.0	256	1.0	1.4	414
P6KE350	315	385	1.0	284	1.0	1.2	504
P6KE350A	333	368	1.0	300	1.0	1.2	482
P6KE400	360	440	1.0	324	1.0	1.0	574
P6KE400A	380	420	1.0	342	1.0	1.1	548
P6KE440	396	484	1.0	356	1.0	0.95	631
P6KE440A1	442	462	1.0	376	1.0	1.0	602
P6KE440A	418	462	1.0	376	1.0	1.0	602
P6KE480	432	528	1.0	389	1.0	0.88	686
P6KE480A	456	504	1.0	408	1.0	0.91	658
P6KE510	459	561	1.0	413	1.0	0.82	729
P6KE510A	485	535	1.0	434	1.0	0.86	698
P6KE540	486	594	1.0	437	1.0	0.78	772
P6KE540A	513	567	1.0	459	1.0	0.81	740